

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS
IIN-D412-698 REV. E OR LATER APPROVED REVISION

REF. TCCA STC: SH92-43
REF. FAA STC: SR01446NY
REF. EASA STC: EASA.IM.R.S.00709
REF. BRASIL STC: 2010S10-09

1.0 PURPOSE:

The purpose of this DSI is to add the optional automatic door opener kit for both the OEM aluminum (Bell P/N 205-031-423-005/-157/-006/-158) and Dart Spacedoor™ (Dart P/N D412-694-03/-04) hinge panel doors.

2.0 DESCRIPTION:

The Dart D412-698-XXX Hinge Panel Automatic Door Opener Kit permits the installation of a gas spring between the hinge panel doors (or "quarter" doors) and the cabin ceiling to prevent the doors from closing while the occupants enter or exit the aircraft.

The **D412-698-041 Hinge Panel Automatic Door Opener Kit** installs on the LH side of the aircraft and the **D412-698-042 Hinge Panel Automatic Door Opener Kit** installs on the RH side of the aircraft. These kits are designed to mount onto the OEM aluminum door (Bell P/N 205-031-423-005/-157/-006/-158).

The **D412-698-043 Hinge Panel Automatic Door Opener Kit** installs on the LH side of the aircraft and the **D412-698-044 Hinge Panel Automatic Door Opener Kit** installs on the RH side of the aircraft. These kits are designed to mount onto the Dart Spacedoor™ (Dart P/N D412-694-03/-04).

LOCATION OF D412-698-042/-044
AUTOMATIC DOOR OPENER

FIGURE 1: LOCATION OF HINGE PANEL AUTOMATIC DOOR OPENER KITS
(RH Installation Shown, LH Opposite)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: *D. Shepherd*
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

A	NEW ISSUE	DC	11.04.26
REV.	DESCRIPTION	BY	DATE
DESIGN	<i>DC</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	<i>DC</i>		
CHECKED	<i>DC</i>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 1 OF 8
APPROVED	<i>DC</i>	TITLE	SCALE
DE APPR.	<i>DC</i>	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

3.0 INSTALLATION OF D412-698-041/-042 HINGE PANEL AUTOMATIC DOOR OPENER (OEM ALUMINUM DOOR):

NOTE: The following instructions are for a typical RH side installation. For installation on the LH side, substitute D4330-041 for D4330-042.

1. Remove any ceiling or trim panels located on the RH foward cabin ceiling. Remove existing door spring Bell p/n 205-030-303-101 and associated hardware.
2. Using Figures 2 and 3 and dimensions shown as reference, locate D4330-042 Airframe Bracket Assembly, RH on the intersection of the existing aircraft rivet lines. The angled part of D4330-042 Airframe Bracket Assembly, RH is required to pick up on a minimum of 3 rivets. The bracket may be hand formed as necessary to improve fit with the contoured ceiling.
3. Mark the location of D4330-3 Door Bracket on the Hinge Panel Door as shown in Figure 4.
4. Verify that the D3552-21 Gas Spring will close properly (0.25" travel before it is fully retracted) when the door is closed. Adjust the position of the D4330-042 Airframe Bracket Assembly, RH if required to maintain rivet edge distance.
5. Verify that the D3552-21 Gas Spring will open the door to the desired position. Ensure the Gas Spring does not interfere with the door or airframe. Adjust location of D4330-3 Door Bracket if required.
NOTE: When the door is fully open, it should be approximately perpendicular to the aircraft.
6. Remove the 205-031-423-005/-157/-006/-158 aluminum door from the aircraft per the Aircraft Maintenance Manual.
7. Remove any existing rivets where the D4330-042 Airframe Bracket Assembly, RH and D4330-3 Door Bracket will be installed.
8. Locate D4330-042 Airframe Bracket Assembly, RH on the aircraft ceiling per Figure 3. Transfer drill #30 ($\phi 0.129$ ") holes from the ceiling to D4330-042. Deburr holes.
9. Locate D4330-3 Door Bracket on the hinge panel door per Figure 4. Using Figure 5 as a guide for the approximate locations of the mounting holes, transfer drill 3x #30 ($\phi 0.129$ ") holes from the door skin to D4330-3 and drill 2x additional holes at locations shown in Figure 5. Deburr holes.
10. Apply a thin layer of Proseal 890 (or equivalent) to faying surface of the D4330-042/-3 brackets. Install the D4330-042 Airframe Bracket Assembly, RH using CR3213-4 rivets as shown in Figure 3. Install D4330-3 Door Bracket using CR3213-4 rivets as shown in Figure 4.
11. Re-install any ceiling or trim panels that were removed in Step 1.
12. Install a D3622-1 Ball Stud on the D4330-3 Door Bracket using hardware specified in Figure 4.
13. Re-install modified door on aircraft per Aircraft Maintenance Manual.
14. Install D3552-21 Gas Spring onto the D3622-1 Ball Studs per Figure 2.
15. Verify proper gas spring and door operation.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: D. Shepherd
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	DC	DART AEROSPACE LTD	
DRAWN	DC	HAWKESBURY, ONTARIO, CANADA	
CHECKED	DE	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 2 OF 8
APPROVED	AA	TITLE	SCALE
DE APPR.	AA	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

4.0 INSTALLATION OF D412-698-043/-044 HINGE PANEL AUTOMATIC DOOR OPENER:

NOTE: The following instructions are for a typical RH side installation. For installation on the LH side, substitute D4330-041 for D4330-042.

1. Remove any ceiling or trim panels located on the RH foward cabin ceiling. Remove existing door spring Dart p/n D3113-1 and associated hardware.
2. Using Figures 2 and 3 and dimensions shown as reference, locate D4330-042 Airframe Bracket Assembly, RH on the intersection of the existing aircraft rivet lines. The angled part of D4330-042 Airframe Bracket Assembly, RH is required to pick up on a minimum of 3 rivets. The bracket may be hand formed as necessary to improve fit with the contoured ceiling.
3. Mark the location of D4330-3 Door Bracket on the Spacedoor™ as shown in Figure 6.
4. Verify that the D3552-21 Gas Spring will close properly (0.25" travel before it is fully retracted) when the door is closed. Adjust the position of the D4330-042 Airframe Bracket Assembly, RH if required to maintain rivet edge distance.
5. Verify that the D3552-21 Gas Spring will open the door to the desired position. Ensure the Gas Spring does not interfere with the door or airframe. Adjust location of D4330-3 Door Bracket if required.
NOTE: When the door is fully open, it should be approximately perpendicular to the aircraft.
6. Remove the D412-694-03/-04 Door Assembly from the aircraft per ICA-D412-694 Section 52.1.
7. Remove any existing rivets where the D4330-042 Airframe Bracket Assembly, RH will be installed.
8. Locate D4330-042 Airframe Bracket Assembly, RH on the aircraft ceiling per Figure 3. Transfer drill #30 ($\phi 0.129"$) holes from the ceiling to D4330-042. Deburr holes.
9. Locate D4330-3 Door Bracket on the Spacedoor™ per Figure 6. Using Figure 7 as a guide for the approximate locations of the mounting holes, drill 3x #7 ($\phi 0.201"$) holes in D4330-3 and the inner door skin. Enlarge holes in Spacedoor™ inner skin to 9/16" ($\phi 0.5625"$).
10. Install the 3x 80-005-2-8 inserts per Paragraph 3.2.12 of the BHT-MED-SRM at the locations drilled in Step 9 in in the Spacedoor™ using Hysol EA934NA.
11. Apply a thin layer of Proseal 890 (or equivalent) to faying surface of the D4330-042/-3 brackets. Install the D4330-042 Airframe Bracket Assembly, RH using CR3213-4 rivets as shown in Figure 3. Install D4330-3 Door Bracket using hardware as shown in Figure 6.
12. Re-install any ceiling or trim panels that were removed in Step 1.
13. Install a D3622-1 Ball Stud on the D4330-3 Door Bracket using hardware specified in Figure 6.
14. Re-install modified door on aircraft per ICA-D412-694 Section 52.2.
15. Install D3552-21 Gas Spring onto the D3622-1 Ball Studs per Figure 2.
16. Verify proper gas spring and door operation.

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: M. Shepherd
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	<u>BC</u>	DART AEROSPACE LTD	
DRAWN	<u>BC</u>	HAWKESBURY, ONTARIO, CANADA	
CHECKED	<u>BC</u>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 3 OF 8
APPROVED	<u>BC</u>	TITLE	SCALE
DE APPR.	<u>BC</u>	HINGE DOOR OPENER KIT	NTS
DATE 11.04.26		COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	




FIGURE 2: INSTALLATION DETAIL
(RH Installation Shown, LH Opposite)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
BY: *[Signature]*
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	<i>BC</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	<i>BC</i>		
CHECKED	<i>[Signature]</i>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 4 OF 8
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	




FIGURE 3: LOCATION OF D4330-042 AIRFRAME BRACKET ASSEMBLY
(RH Shown, LH Opposite)





FIGURE 4: LOCATION OF D4330-3 DOOR BRACKET (OEM ALUMINUM DOOR)
(RH Shown, LH Opposite)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
BY: *[Signature]*
D. SHEPHERD (DE # 02)
DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	<i>DC</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	<i>DC</i>		
CHECKED	<i>DS</i>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 5 OF 8
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	



**FIGURE 5: LOCATION OF D4330-3 DOOR BRACKET MOUNTING HOLES
(OEM ALUMINUM DOOR)**

(NOTE: MAINTAIN MINIMUM EDGE DISTANCE OF 0.25" FROM HOLE CENTER)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: *[Signature]*
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	<i>BC</i>	DART AEROSPACE LTD	
DRAWN	<i>BC</i>	HAWKESBURY, ONTARIO, CANADA	
CHECKED	<i>[Signature]</i>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 6 OF 8
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	




FIGURE 6: LOCATION OF D4330-3 DOOR BRACKET (SPACEDOOR™)
(RH Shown, LH Opposite)




FIGURE 7: LOCATION OF D4330-3 DOOR BRACKET MOUNTING HOLES
(SPACEDOOR™)

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED
BY: *[Signature]*
D. SHEPHERD (DE # 02)
DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	<i>BC</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	<i>BC</i>		
CHECKED	<i>DE</i>	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 7 OF 8
APPROVED	<i>[Signature]</i>	TITLE	SCALE
DE APPR.	<i>[Signature]</i>	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	

5.0 WEIGHT & BALANCE:

INSTALLATION	WEIGHT	LATERAL		LONGITUDINAL	
		Arm	Moment	Arm	Moment
D412-698-041 LH (Standard)	0.23 lb 0.10 kg	-43.63 in -1.11 m	-10.03 in-lb -0.11 m-kg	86.27 in 2.19 m	19.84 in-lb 0.22 m-kg
D412-698-042 RH (Standard)	0.23 lb 0.10 kg	43.63 in 1.11 m	10.03 in-lb 0.11 m-kg	86.27 in 2.19 m	19.84 in-lb 0.22 m-kg
D412-698-043 LH (Spacedoor™)	0.23 lb 0.10 kg	-43.63 in -1.11 m	-10.03 in-lb -0.11 m-kg	86.27 in 2.19 m	19.84 in-lb 0.22 m-kg
D412-698-044 RH (Spacedoor™)	0.23 lb 0.10 kg	43.63 in 1.11 m	10.03 in-lb 0.11 m-kg	86.27 in 2.19 m	19.84 in-lb 0.22 m-kg

6.0 PARTS LIST:

Qty -041	Qty -042	Qty -043	Qty -044	Part Number	Description
X				D412-698-041	HINGE PANEL AUTOMATIC DOOR OPENER KIT, LH (STANDARD)
	X			D412-698-042	HINGE PANEL AUTOMATIC DOOR OPENER KIT, RH (STANDARD)
		X		D412-698-043	HINGE PANEL AUTOMATIC DOOR OPENER KIT, LH (SPACEDOOR™)
			X	D412-698-044	HINGE PANEL AUTOMATIC DOOR OPENER KIT, RH (SPACEDOOR™)
1	1	1	1	D3552-21	GAS SPRING
1	1	1	1	D3622-1	BALL STUD
1		1		D4330-041	AIRFRAME BRACKET ASSEMBLY, LH
	1		1	D4330-042	AIRFRAME BRACKET ASSEMBLY, RH
1	1	1	1	D4330-3	DOOR BRACKET
		3	3	80-005-2-8	INSERT
1	1	1	1	MS21042L5	NUT
		3	3	MS27039-1-05	SCREW
		3	3	NAS1149D0332J	WASHER
1	1	1	1	NAS1149D0563J	WASHER

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

APPROVED

BY: 
D. SHEPHERD (DE # 02)

DATE: 11.04.26
CERT. NO.: SH92-43
ISSUE NO.: 5

DESIGN	DC	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	DC		
CHECKED	BE	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9548	SHEET 8 OF 8
APPROVED	HH	TITLE	SCALE
DE APPR.	HH	HINGE DOOR OPENER KIT	NTS
DATE	11.04.26	COPYRIGHT © 2011 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	